



AURORA®

Aurora Pump provides fire protection pumping for a variety of solutions throughout the world.

With over ninety years of experience, Aurora's commitment to excellence goes beyond the product line by being dedicated to keeping our customers, distributors and employees constantly educated and updated on the leading developments in fire protection. Our computer software programs assist with selecting the best pumps and systems along with providing pump drawings and specifications. These programs save valuable time in the selection and evaluation of pumps and systems.

As an ISO 9001 registered company, Aurora Pump is committed to quality. In addition, to meet your time-critical requirements, Aurora offers the Red Hot quick ship program for total fire pump packages. Along with our outstanding customer service, Aurora will keep your fire pump system at peak performance for years to come. You can rely on Aurora Pump and our qualified distribution network to provide total pump solutions for fire protection.



Pictured at top: Packaged Fire Pump System.

Pictured at bottom: Typical housed diesel driven fire pump with test meter.

Vertical Inline



Model 383

Single Stage Inline Fire Pump

Flows: 50 to 1,500 GPM (11.3 to 340 $\rm m^3/hr$) Pressures: 40 to 159 PSI (2.7 to 11 bar)

- UL Listed/FM Approved/NFPA-20 Design
- Space Saving Vertical Design
- Easy Maintenance without Disturbing Surrounding Piping
- Bronze-Fitted Pump Construction

End Suction



Model 384

End Suction Fire Pump

Flows: 50 to 1500 GPM (11.3 to 340 m 3 /hr) Pressures: 40 to 225 PSI (2.7 to 15.5 bar)

- UL Listed, FM Approved Performance
- Electric and Diesel Speeds
- Back Pullout Design for Easy Pump Service without Disconnecting Pipe
- Frame-Mounted Design
- Small Footprint Ideal for Retrofit
- Designed for Installations such as Schools, Office Buildings and Hospitals

Horizontal Split Case



Models 481, 485, 491, 492, 495

Horizontal Split Case Electric Drive Fire Pumps

Flows: 250 to 5,000 GPM (56.8 to 1135 $\rm m^3/hr$) Pressures: 40 to 435 PSI (2.7 to 30 bar)

- UL Listed/FM Approved/NFPA-20 Design
- For Commercial, Industrial and Marine Use
- Diesel and Electric Driven Available
- Lower Initial Cost
- Quicker Delivery with Red Hot Quick Ship Program
- Ease of Maintenance

Fire Pumps and Systems

Vertical Split Case

Diesel-Driven Split Case

Vertical Turbine



Model 483

Vertical Split Case Electric Drive Fire Pump

Flows: 250 to 2,500 GPM (56.8 to 568 m³/hr) Pressures: 40 to 200 PSI (2.7 to 13.8 bar)

- UL Listed/FM Approved/NFPA-20 Design
- · For Commercial, Industrial and Marine Use
- Electric Driven Available
- Lower Initial Cost
- · Ease of Maintenance



Models 481, 485, 491, 492, 495

Horizontal Split Case Diesel Drive Fire Pumps

Flows: 250 to 5,000 GPM (56.8 to 1,135 m³/hr) Pressures: 40 to 435 PSI (2.8 to 30 bar)

- UL Listed/FM Approved/NFPA-20 Design
- For Commercial, Industrial and Marine Use
- Diesel and Electric Driven Available
- Lower Initial Cost
- Quicker Delivery with Red Hot Quick Ship Program
- Ease of Maintenance



Fire Pump Vertical Turbine

Flows: 250 to 4,500 GPM (56.8 to 1,022 m³/hr) Pressures: 50 to 370 PSI (3.4 to 25.5 bar)

- UL Listed/FM Approved/NFPA-20 Design
- For Commercial, Industrial and Marine Use
- Special Materials for Seawater Applications
- Diesel and Electric Driven

Jockey Pump



Models PVM & PVMX

Jockey Pumps

Horsepower: 1/2 to 40 Flows: 50 GPM (11.3 m³/hr) Capacities: 215 GPM (48.8 m³/hr) Pressures: 330 PSI (22.7 bar) Heads: 800 Feet (244 m) Temperatures: 250°F (121°C)

- · Space-Saving Design Recommended Where Floor Space Is Extremely Limited
- Available in Cast Iron or 316 Stainless Steel Materials
- Standard TEFC Motor

Packaged System

Packaged Fire Pump Systems

- UL Listed/FM Approved Aurora® Fire Pump
- UL Listed/FM Approved Fire Pump Controller
- ETL Listed
- Aurora Jockey Pump
- UL Listed Jockey Pump Controller
- Pressure Sensing Lines Complete per NFPA 20
- Listed OS & Y Gate & Butterfly Valves with Tamper Switches
- Suction and Discharge Pressure Gauges
- Automatic Casing Air Release Valve
- Casing Pressure Relief Valve (Electric Packages)
- Hose Header with Valves, Caps & Chains
- Suction and Discharge Piping per NFPA 20

• Removable Lifting Lugs

Compact System



Compact Fire Pump Systems

Flows to 750 GPM (170.3 m³/hr) Pressures to 160 PSI (11.0 bar)

- Ideal for Smaller Areas Fits through a 36" Doorway
- · Multiple Starting Methods Available for the Fire Pump with Optional Automatic Transfer Switch
- Optional City Bypass

Fire Pump Houses



- Designed to Meet Specific Environmental Requirements
- All-Steel Building with Seismic Certification
- Easy Access Entries
- Electric Heaters with Built-In Thermostat
- Continuous Duty Exhaust Fan

- AC Motor/Solenoid Operated Louver
- Interior Fluorescent and Flood Light, Exterior 70 W HPS Light
- Sprinkler System per NFPA 13
- Finished through Wall or Floor Penetration
- Single Point Electrical Connection
- State Certification Label

Accessories

- Casing Relief Valve/Air Relief Valve
- Eccentric Suction Reducers, Concentric Discharge Increasers
- Test Manifold, Hose Valves, Ball Drip Valve
- Main Relief Valve, Waste Cone
- Flow Metering Systems
- Diesel Batteries, Racks and Cables
- Double Wall Fuel Tanks and Fittings

- Diesel Engine Mufflers
- Exhaust Flex Connectors
- City Bypass
- Backflow Preventer
- Insulated Exhaust Piping
- Roof Curb for Vertical Turbine Installation and Removal
- Alarms and Tamper Switches Prewired to a Common Junction Box









